



Technical Specifications:

- Rugged machine with ground bed
- 12 station programmable ATC
- Industrial motion controller and have FMS and CIM compatibility.
- X-axis travel : 250 mm
- Y-axis travel : 175 mm
- Z-axis travel : 200 mm
- Table size : 500x200mm minimum
- Spindle nose to table top: 40-190mm
- Spindle to column : 110mm
- Spindle motor: 2 HP motor with 3000RPM
- Resolution: 0.005mm
- Repeatability : ± 0.01 mm
- Programmable feed rate: 0-800mm/mi

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

- Rapid feed rate : 0-1200mm/min
- Control system: PC based system
- Machine dimension : 1200x1200x1800mm approx
- Total weight : 1200kg approx
- Spindle inside Taper : BT 30 / BT 40
- Repeatability : ± 0.01 mm
- Automatic Lubrication Points : Provided
- Lubrication : Centralized (Programmable)

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com