

**Technical Specifications:**

- Overload protection and high precise measurement
- Null DCV: DC  $\pm 5V$  /  $\pm 25V$ ,  $\pm 5\%$  FSD
- DCV: 0.1/2.5/10/50/250V/1000V,  $\pm 4\%$  FSD
- ACV: 10/50/250V/1000V,  $\pm 5\%$  FSD
- DCA: 50 $\mu$ A/2.5mA/25mA/250mA/10A,  $\pm 4\%$  FSD
- Resistance:  $\times 1$  /  $\times 10$  /  $\times 100$  /  $\times 1k$  /  $\times 10k\Omega$  (0.2 $\Omega$  ~ 20M $\Omega$ )
- Capacitance: C1(R $\times 1k$ ): 2000 $\mu$ F (Approx.) Max
- Battery Check: 1.5V/9V
- Transistor hFE, Diode and LED Test facility
- Continuity with Beeper facility
- Safety Standard: CAT II 1000V and CAT III 500V
- Standard accessories with printed operation manual
- Warranty: 1(One) year with services

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com



- Documents: Catalogue should be submitted



Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com

