

**Technical Specifications:**

- 3 3/4 True RMS multimeter
- DCV range: 400mV/40/400V, 1000V
- ACV range: 400mV, 4/40/400/750V
- DCA range: 400 $\mu$ /4000 $\mu$ A, 40m/400mA, 10A
- ACA range: 400 $\mu$ /4000 $\mu$ /40m/400mA, 10A
- Resistance: 400 $\Omega$ , 4k/40k/400k/4M $\Omega$ , 40M $\Omega$
- Capacitance: 10n, 100n/1 $\mu$ /10 $\mu$ /100 $\mu$ F, 1/10/100mF
- Frequency: 100/1000/10k/100kHz, 1M/30MHz
- Temperature: -20~400°C, 400~1000°C
- Continuity with beeper
- Diode & transistor test facility
- Data hold & auto power off function
- LCD backlight and low battery indication
- Safety Standard: CAT IV 600V

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com



- Power: 9V battery
- Accessories: Test lead, Transistor test socket, Thermocouple probe and operation manual
- Warranty: 1(One) year with services
- Documents: Catalogue should be submitted

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com