



FEATURES:

- Microcomputer technology is used for fast and accurate measurement.
- Memory button recalls the last, Min and Max values during measuring period.
- Wide measuring range, high resolution and high reliability.
- Measurements can be read as RPM, meters /min or feet/min.
- Auto zero adjustment.
- New streamline plastic casing, designed to fit comfortably in either hand.
- Supplied with an interchangeable rubber cone tip for shaft rotation measurement and rubber wheel for surface speed measures

SPECIFICATIONS:

- Measuring Range : 5-19,999 RPM,
0.05-1,999.9 m/min (0.2-6,560 ft/min)
- Resolution : 0.1 RPM (<1000 RPM)
1.0 RPM (1000 RPM)
- Accuracy : $\pm 0.05\% + 1 \text{ dgt}$
- Sampling time : 1 Sec. (over 6 RPM)
- Dimensions : 190x72x37mm
- Weight : approx. 200g
- Accessories : rubber wheel and rubber cone tip

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in

