



Features

- Unit : Electric Field - V/m
Magnetic Field - μ T
- Precision : Electric Field - 1 V/m
Magnetic Field - 0.01 μ T
- Alarm threshold value : Electric Field - 40 V/m
Magnetic Field - 0.04 μ T
- Testing bandwidth : 5Hz-3500MHz
- Sampling time : About 0.4 seconds
- Test mode : Bi-module Synchronous Test
- Over range indication : LCD display 1

Technical Specifications

Type of Product	:	Electromagnetic Radiation Tester
Display	:	3 ½ digit LCD Display
Operating Temperature	:	0°C - 50°C
Relative Humidity	:	<80%RH
Power Input	:	6F22 9V Battery
Weight	:	146g
Dimension In mm (LXWXH)	:	63.6 x 31 x 125.8 mm
Voltage	:	9 V
Measurement Range	:	1V/m-1999V/m

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tescaglobal.com