



### Specification

Model	17042	17043	17044	17045
Output voltage	0~30V			
Output current	0~10A	0~2A	0~3A	0~5A
Source regulation	$1 \times 10^{-4} + 3mV$			
Load regulation	$1 \times 10^{-4} + 3mV$			
Ripple & noise	1mV			
Display error	0.5%+1 digit			

Voltage		0 to Nominal Value Continuously Variable
	Stability	Voltage: 0.01%+2mV Load: 0.0%+2mV
	Recover Time	100mS
	Ripple & Noise	1MVRMSefficient
	Temperature Factor	300PPM/°C
Current		0 to Nominal Value Continuously Variable
	Current, Load Stability	0.2%+3mA
	Ripple & Noise	3mArms
Working Condition	Line Power Supply	220V±10% 50/60Hz (Alterable if needed :110±10%50/60Hz)
	Operating	Temperature:-10°C~40°C Moisture 90%
	Storage	Temperature:-20°C~80°C Moisture 80%

Note: Specifications are subject to change.

**Tesca Technologies Pvt. Ltd.**

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,  
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,  
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com  
Website: www.tesca.in