

Safety Features

- Battery powered; Model 19522 battery + mains powered
- Test voltages of 2500V;5000V;10,000V DC
- Resistance up to 400 Giga ohm
- Dual color coded scales for high and low resistances
- Automatic change of high and low resistances ranges
- Low power consumption
- Hard carrying case with test leads



Specifications:

Model : 19522 is same as 19521 except that this model can also be used power supply of mains 220V AC, 50Hz.

Model		19521		19523	
DC Test Voltage		2500V	5000V	5000V	10000V
Measuring Ranges		0-2 Gohm 1-100 Gohm (automatic change)	0-5 Gohm 2-200 Gohm (automatic change)	0-5 Gohm 2-200 Gohm (automatic change)	0-10 Gohm 4-400 Gohm (automatic change)
Accuracy	Insulation Resistance	±5% of reading (0.1-50 Gohm) ±10% of reading or 0.5% of scale length (ranges other than listed above) at 18-28°C ±10% of reading (0.1-50 Gohm) ± 20% of reading or 1.0% of scale length (ranges other than listed above) at -10 to + 40°C	±5% of reading (0.2-100 Gohm) ±10% of reading or 0.5% of scale length (ranges other than listed above) at 18-28°C ±10% of reading (0.2-100 Gohm) ± 20% of reading or 1.0% of scale length (ranges other than listed above) at -10 to + 40°C	±5% of reading (0.2-100 Gohm) ±10% of reading or 0.5% of scale length (ranges other than listed above) at 18-28°C ±10% of reading (0.2-100 Gohm) ±20% of reading or 1.0% of scale length (ranges other than listed above) at -10 to + 40°C	±5% of reading (0.4-200 G) ±10% of reading or 0.5% of scale length (ranges other than listed above) at 18-28°C ±10% of reading (0.4-200 Gohm) ±20% of reading or 1.0% of scale length (ranges other than listed above) at -10 to + 40°C
	Output± Voltage	2500V±5% (0.1-50 Gohm)	5000± 5% (0.2-200 Gohm)	5000V±5% (0.2-100 Gohm)	10,000V±5% (0.4-200 Gohm)
Operating Temperature: - 10°C ± 40°C at 85% max Relative humidity					
Storage Temperature & Humidity: - 20°C + 60°C at 90% max Relative humidity					
Insulation Resistance : 1000M max / 1000V between electrical circuit and housing case					
Withstand Voltage: 5000V AC for one minute between electrical circuit and housing case					
Dimensions: 200 (L) x 140 (W) x 80 (D) mm					
Weight: Approx Lkg (Including batteries & line probe)					
Power source: 8 pcs of 1.5V SUM -3 battery of equivalent; 19522 besides battery, is also powered by mains 220V AC.					
Accessories : Hard Carrying case, Batteries, Test leads (Earth & Guard leads)					

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in