


**Features:**

- Thin, light, compact body design for one-hand operation
- 18mm triangular jaw allows for easy measurement on small cables
- Large, easy-to-read backlit display
- 200 A ac and dc current and 600 V ac and dc voltage measurement range
- 3000  $\Omega$  resistance range, continuity detection
- Zero function allows the display to be cleared for DC measurements
- Data Hold function
- CAT III 600 V safety rating

**Specifications:**

	Range	Resolution	Accuracy
AC current	200A	0.1A	2% $\pm$ 5 digits (45-65Hz) 2.5% $\pm$ 5 digits (65-400Hz)
DC current	200A	0.1A	2% $\pm$ 5 digits
AC voltage	600 V	0.1 V	1.5% $\pm$ 5 digits (45-400Hz)
DC voltage	600 V	0.1 V	1% $\pm$ 5 digits
Resistance	300/3000 $\Omega$	0.1/1 $\Omega$	1% $\pm$ 5 digits
Continuity	$\leq 70\Omega$		

  

General Specifications	
Size (LxWxH) mm	205 $\times$ 60 $\times$ 22
Clamp opening	18 mm
Weight	196 g
Safety rating	CAT III 600 V

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com