



### Features:

- Pocket size, compact design
- Measures: air velocity, temperature, humidity, dew point, wet bulb, wind-chill and ambient temperature
- Selectable wind units: KNT (Knot), BF (Beaufort), ft/m (feet per minute), M/h (mile per hour), m/s (meter per second), km/h (kilometer per hour)
- Selectable temperature units °C or °F
- Max wind speed display
- Quick measurement response
- External temperature probe
- Easy, two-button operation
- Data hold
- Auto power off with disable feature
- Low battery indication
- Ergonomic design with a wrist strap

### Specifications:

Specifications	
Wind speed range:	0.5 – 44.7 MPH, 60 – 3937 FT/M, 0.4-38.8KNT, 1.1-20.0 M/S, 0.7-72.0KMH, 1-8 BF
Wind speed accuracy:	+/-5% of reading or last significant digit (whichever is greater)
Air temperature range:	0°C to 50°C (32°F to 122°F)
Air temperature resolution:	0.1°C/°F
Air temperature accuracy:	+/-1°C (+/- 30.2°F to 33.8°F)

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
[www.tescaglobal.com](http://www.tescaglobal.com)

External temperature range:	-20°C to 70°C (-4°F to 158°F)
External temperature resolution:	0.1°C/°F
External temperature accuracy:	+/-0.6°C (+/- 31°F to 33.1°F) (-20°C to 50°C / -4°F to 122°F), other ranges +/-1.2°C (29.8°F to 34.2°F)
Air RH% range:	5%RH to 95% RH
Air RH% resolution:	0.1% RH
Air RH% accuracy:	+/-3.5% RH (at 25C, 10 – 90% RH, other ranges +/- 5% RH)
Wind speed response:	Averaging every 2 seconds
Temperature response time:	60 seconds (typical)
Air RH% response time:	60 seconds (typical)
LCD update:	Every second
Wind-chill display:	Yes
Dew point temperature:	Yes
Wet bulb temperature:	Yes

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
[www.tescaglobal.com](http://www.tescaglobal.com)

CIN: U29309RJ2011PTC035213  
 GSTIN: 08AADCT8576E1ZZ

Follow Tescaglobal



worlddidac  
 MEMBER

