

Order Code - 22235424.3 Digital Theodolite



Description:

With Optical plummet Having 1" least count and 2" accuracy, 30x Magnification along with all standard accessories:-

Standard Accessories Battery Charger (01 No.) Chargeable Battery (01 Nos.) Pencil Cell Battery (01 No.) Operation Manual (01 No.) Tool Kit (01 No.) Carrying Case (01 No.) Plum Bob (01 No.)

Aluminum Tripod (01 No.) Included

Telescope	Image	Positive
	Magnification Ratio	30×
	Effective Aperture of Object Lens	45mm
	Angle of View	1 30'
	Shortest Visibility Distance	0.5m
	Stadia Multiplication Constant	100
	Stadia Addition Constant	0
	Resolution	3"
Angle Measuring System	Mode of Angle Measurement	Photoelectric Incremental
	Min. Reading	Reading 1" 5" 10 "Selectable
	Detection Method	H: Both Sides
		V: Single Side
	Precision of Angle Measurement	2''
	Unit of Angle	DEG MIL GON
	Display	LCD Double Side

Specifications :

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



India Sales: +91-9588842361

Export Sales: +91-9829132777

♀ IT-: Sita

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302022, India. info@tesca.in www.**tescaglobal**.com

CIN: U29309RJ2011PTC035213 GSTIN: 08AADCT8576E1ZZ Follow Tescaglobal 🕜 🙆 🕐 in 🖗





Order Code – 22235424.3 Digital Theodolite

Compensator	Tilt Sensor	Automatic vertical compensation
		YES
	Range of Compensation	±3'
Optical plummet	Image	Positive
	Magnification Ratio	3×
	Angle of View	5°
	Focusing Range	0.5m~∞
Sensitivity of vial	tubular vial	30''/2mm
	circular vial	8'/2mm
Ambient Temperature		-20°C ~ +50°C
Power Supply	Battery	Rechargeable Ni-H Battery
	Source Voltage	6V
	Duration of Operation	16h
Weight of Instrument		5kg
Dimensions		164×154×340mm

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.

