

**Specifications :**

- Gearless pillar drilling machine

<b>DRILLING CAPACITY</b>	<b>13 MM</b>
<b>SPINDLE SPEED</b>	<b>FOUR SPEED</b>
<b>SPEED RANGE</b>	<b>650 TO 2400</b>
<b>SPINDLE NOSE</b>	<b>6-J TAPPER</b>
<b>SPINDLE CENTRE TO COLUMN</b>	<b>150 MM</b>
<b>SPINDLE TRAVEL</b>	<b>75 MM</b>
<b>MAXI. DISTANCE SPINDLE TO TABLE</b>	<b>450 MM</b>
<b>MAXI. DISTANCE SPINDLE TO BASE</b>	<b>650 MM</b>
<b>WORKING SURFACE OF BASE</b>	<b>240 X 190</b>
<b>WORKING SURFACE OF TABLE</b>	<b>205 MM</b>
<b>COLUMN DIAMETER</b>	<b>47 MM</b>
<b>MACHINE BASE</b>	<b>300 X 200</b>
<b>MOTOR / RPM</b>	<b>0.5 HP / 1440 RPM</b>

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com