

**Specification:-**

- The Tyre changer operate with electro pneumatic power. The mounting head is made of special steel and patent design. It fits in all type of Rim Profiles. The machine is designed to handle wide rims efficiently.
- 24 Inch Turn Table of 14 mm thickness.
- 40 Ampere Silver Point Reverse Switch
- 1.5 HP High Torque imported copper winding motor
- Heavy Duty Gear Box with non-wearing mixed steel material gears
- Alloy Wheel ready machine with rubber cover on mounting device, on Wheel Clamps, on Bead breaking shovel
- Heavy Duty Large Size long life industrial grade FRL.
- Independently connected Tyre Pressure Gauge with Hose
- All pneumatic pipes connected with end nuts to avoid air leakage in spring type connectors
- More than 1000 Tyre changers running across the countr
- Rim Clamping from Outside : 10"~18"
- Rim Clamping from Inside : 12"~21"
- Max wheel diameter : 960 mm
- Max wheel width : 3-12"
- Operation Pressure : 8-10 bar
- Motor Power : 1.5 HP
- Bead breaking force : 2500 kg
- Noise Level : <70 db

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com