

**Specification:-**

- Electro Hydraulic Two Post Lift. It is manufactured with advanced technologies using high precision CNC machines & quality material. It adopts hydraulic power unit and oil nylon roller structure, achieving smooth and steady lifting with low noise. It is equipped with a falling prevention support, a lifting arm gyro angle lock unit and a bracket steel rope forced synchronization unit. The maintenance is simple and the operation is convenient. Strict pre-dispatch inspection is done for all machines.
- Bilateral Manual Safety Unlocking System
- The cable and oil pipe are fully concealed
- Double Hydraulic cylinder and high strength chain drive makes stable and smooth lifting
- Wire rope equalization system forces synchronous movement of two carriages and effectively prevents the vehicle from tilting
- Lifting Pads with different heights meets the requirement for high and low chassis vehicles
- Passed 115% dynamic loading test and 150% static loading test
- Lifting Capacity : 4000 Kg.
- Lifting Height : 1800 mm
- Width : 2690 mm
- Power Supply : 220V, 50Hz, 1 Phase

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com