

**Specification :-**

- DIFFERENTIAL FEED RATIO :
For gathering : 1:2 (Max. 1:4)
For stretching : 1:0.7 (Max. 1:0.6)
- DIRECT-DRIVE MOTOR : 400W
- INCLINATION ANGLE OF THE NEEDLE : 20°
- LIGHT LED : needle light
- LUBRICATION : Automatic
- MACHINE LEVEL : Standard
- MACHINE TYPE : Overlock
- MAX LIFT OF THE PRESSER FOOT : 5mm
- MAX PRESSER FOOT PRESSURE : 63.7N (6.5kgf)
- MOTOR TYPE : Direct-drive
- NEEDLE BAR STROKE : 24.5mm
- NEEDLE COOLER : Provided as standard
- NEEDLE POSITION : Yes, Up & Down Function
- NEEDLE SYSTEM : B 27 81x1 DCx21
- NEEDLE THREAD HEAT REMOVER : Provided as standard
- NUMBER OF THREADS : 4
- OVEREGGING WIDTH : 3,0 4,0mm
- POWER REQUIREMENT : Single-phase 220V~240V 13 amp (can be used at home)
- STITCH LENGTH (MM) : 0.6 ~ 3.8
- TYPE : 1-needle overlock
- WEIGHT OF THE MACHINE HEAD : 27kg
- MAX SEWING SPEED (STI/MIN) : 5,500

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com