



Specifications:-

- Supported Sample Rates
- 44.1khz, 48khz, 88.2khz, 96khz, 176.4khz, 192khz Microphone Inputs
- Frequency Response : 20hz ? 20khz ± 0.1db
- Dynamic Range : 111db (A-weighted)
- Thd+N : <0.0012%
- Noise Ein : -128dB (A-weighted)
- Maximum Input Level : 9dbu (at A Minimum Gain)
- Gain Range: 56db
- Impedance: 3k ω
- Line Inputs Frequency Response : 20hz 20khz ± 0.1db
- Dynamic Range : 110.5db (A-weighted)
- Thd+N : <0.002%
- Maximum Input Level : 22dbu (at Minimum Gain)
- Gain Range : 56db
- Impedance : 60k ω instrument Inputs
- Frequency Response : 20hz ? 20khz ± 0.1db
- Dynamic Range : 110db (A-weighted)
- Thd+N : <0.03%
- Maximum Input Level : 12.5dbu (at Minimum Gain)
- Gain Range : 56db
- Impedance : 1.5m ω line/Monitor Outputs
- Dynamic Range (Line Outputs) : 108db
- Thd+N : <0.002%

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com

- Maximum Output Level (0 Dbfs) : 15.5dbu
- Impedance : 430 ω headphone Outputs
- Dynamic Range : 104db (A-weighted)
- Thd+N : <0.002%
- Maximum Output Level : 7dbu
- Impedance : <1 Ω
- Standard Packaging For Export.



Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com