

**Specifications:-**

- Minimum Switching Current: 10 mA
- Maximum Switching Voltage: 250 V AC, 28 V DC
- Minimum Switching Voltage: 17 V
- Load Current: 5 A At 250 V AC, 5 A At 28 V DC
- Maximum Switching Capacity: 1250 VA Ac, 140 W DC
- Minimum Switching Capacity: 170 mW
- Operating Rate:  $\leq 1200$  Cycles/Hour Under Load,  $\leq 18000$  Cycles/Hour No-Load
- Mechanical Durability: 10000000 Cycles
- Electrical Durability: 100000 Cycles For Resistive Load, 50000 Cycles, 1 A At 28 V, Dc-13 NO
- Average Coil Consumption In VA: 1.2 Ac
- Drop-Out Voltage Threshold:  $\geq 0.15$  Uc AC
- Operating Time: 20 ms Between Coil De-Energisation And Making Of The Off-Delay Contact, 20 ms Between Coil Energisation And Making Of The On-Delay Contact
- Average Resistance: 16500 Ohm At 23 °C +/- 15 %
- Rated Operational Voltage Limits: 184-253 V AC

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com