



Compliance Standards:

ASTM D5199, ASTM D 5199, BS EN 964, ISO 9863, ASTM D1777-99,

Applications:

To control the physical properties of Geotextile and Geosynthetic Material.

Details:

- Dead weight panel is provided to apply desired pressure varying from 50, 100 and 200 kpa
- Surface plate is grounded and is rust free to enable reproducible results
- Fitted with precise and accurate Mitutoyo thickness gauge
- Digital indicator is easy to use while also being quick and efficient.
- **Carbide disc contact points**
- Protection Rating IP42
- Data hold
- Counting direction switchable
- Battery SR 44 or LR 44

Function of Digital Models (IDC Type)

- ON/OFF
- Inch/mm Conversion
- Zero/ABS
- ±Direction Changeover
- SPC Output
- Battery Life : 5,000 hrs
- Power Supply : Silver Oxide Cell (SR-44 1pc.)
- Preset
- Provides GO/±NG Judgment
- Face Rotates 330°

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com