

**Specifications:-**

- Number Of Channels : 1
- Total Supply Voltage (Max) (+5V=5, +/-5V=10) : 44
- Total Supply Voltage (Min) (+5V=5, +/-5V=10) : 10
- Rail-To-Rail : No
- Gbw (Typ) (Mhz) :1
- Slew Rate (Typ) (V/us) : 0.5
- Vos (offset Voltage @ 25 C) (Max) (mV) : 3
- Iq Per Channel (Typ) (mA) : 1.7
- Vn At 1 Khz (Typ) (nV/rtHz) : 30
- Operating Temperature Range (C) : -40 To 85, 0 To 70
- Offset Drift (Typ) (uV/C) : 15
- Input Bias Current (Max) (pA) : 210000
- Cmrr (Typ) (dB) : 90
- Output Current (Typ) (mA) : 25
- Architecture : Bipolar

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.




Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



Specifications:-

- Iq (Typ) (uA) : 2000
- Operating Temperature Range (C) : 0 To 70
- Supply Voltage (Max) (V) : 16
- Supply Voltage (Min) (V) : 4.5

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com