



Specifications:-

Maximum Swing Over Bed	360 mm
Maximum Swing Over Slide	180 mm
Maximum Machining Length	290 mm
Spindle Head Type	A2-5
Spindle Taper Hole	48 mm
Maximum Bar Through Diameter	36 mm
Maximum Spindle Speed	3000 r/min.
Spindle Shift Mode	Frequency Conversion
Spindle Motor Power	4 KW
Chuck Type	Hydraulic Chuck
Chuck Size	6 inch
X-axis Travel	280 mm
Z-axis Travel	400 mm
Rapid Traverse Speed on X-axis	15 m./min
Rapid Traverse Speed on Z-axis	15 m./min
X-axis Motor Torque	4Nm
Z-axis Motor Torque	4Nm
Guideway Type	Linear Guideway
X-axis Linear Guideway Width	30 mm
Z-axis Linear Guideway Width	30 mm
X-axis Screw Diameter/Pitch	25/05 mm
Z-axis Screw Diameter/Pitch	32/06 mm
Tool Type	4 Station Electric Tool Post
Turning Tool Size/Boring Tool Size	20*20/∅ 25mm
Tailstock Type	Manual Tailstock
Tailstock Sleeve Internal Taper	MT-4
Tailstock Sleeve Diameter	50 mm
Tailstock Sleeve Travel	150 mm
Dirriension(L*W*H)	1850*1300*1700 mm
Weight	1200 kg

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com