



Specifications:

• 3/2 valve, Normally Closed (NC), operated by push-button

- 1. Operated by industrial grade push-button, normally in closed position, spring-return.
- 2. Come with ISO symbol on component's body or component's mounted plate.
- 3. One-touch fittings for 4mm tube.
- 4. Quantity: Minimum 2 units

• 3/2 double valve, Normally Closed (NC), operated by switch

- 1. Includes two 3/2 port valve with locking system.
- 2. Operated by switch.
- 3. Come with ISO symbol on component's body or component's mounted plate.
- 4. One-touch fittings for 4mm tube.
- 5. Quantity: Minimum 1 unit

• 3/2 valve, Normally Closed (NC), operated by an emergency knob

- 1. Operated by emergency knob.
- 2. Spring-return.
- 3. Come with ISO symbol on component's body or component's mounted plate.
- 4. One-touch fittings for 4mm tube.
- 5. Quantity: Minimum 1 unit

• FC 3/2 NC valve. Operated by one-way roller lever

- 1. Operated by one-way roller lever
- 2. Come with ISO symbol on component's body or component's mounted plate.
- 3. One-touch fittings for 4mm tube.
- 4. Quantity: Minimum 2 units

• 3/2 single valve, NC/NO, air operated

1. Includes a 3/2 valve, which the user can convert from NO to NC, as required.

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302022, India.















- 2. Provided with a plug for functioning as NO or NC.
- 3. Spring return.
- 4. Manual over-ride.
- 5. Come with ISO symbol on component's body or component's mounted plate.
- 6. One-touch fittings for 4mm tube.
- 7. Quantity: Minimum 2 units

• 5/2 single valve, air operated

- 1. Air operated
- 2. Come with ISO symbol on component's body or component's mounted plate.
- 3. One-touch fittings for 4mm tube.
- 4. Quantity: Minimum 2 units

• 5/2 double valve, air operated

- 1. Air operated
- 2. Come with ISO symbol on component's body or component's mounted plate.
- 3. One-touch fittings for 4mm tube.
- 4. Quantity: Minimum 3 units

Block of 2 x 5/2 double valves + 1 x 5/2 single valve

- 1. A block consists of 3 valves $(2 \times 5/2 \text{ double valves} + 1 \times 5/2 \text{ single valve})$
- 2. Come with ISO symbol on component's body or component's mounted plate.
- 3. One-touch fittings for 4mm tube.
- 4. Quantity: Minimum 1 unit

Double OR valve

- 1. Includes double circuit selector with logic function "OR".
- 2. Come with ISO symbol on component's body or component's mounted plate.
- 3. One-touch fittings for 4mm tube.
- 4. Quantity: Minimum 3 units

Double AND valve

- 1. Includes double simultaneous valve with logic function "AND".
- 2. Come with ISO symbol on component's body or component's mounted plate.
- 3. One-touch fittings for 4mm tube.
- 4. Quantity: Minimum 1 unit

• Single direction speed controller (double)

- 1. Includes two single direction speed controllers.
- 2. Manually adjusted
- 3. Come with ISO symbol on component's body or component's mounted plate.

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777 India Sales: +91-9588842361




IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302022, India.













- 4. One-touch fittings for 4mm tube.
- 5. Quantity: Minimum 1 unit

5/3 double valve with close center, air operated

- 1. Double piloting with memory function.
- 2. Air operated
- 3. Come with ISO symbol on component's body or component's mounted plate.
- 4. One-touch fittings for 4mm tube.
- 5. Quantity: Minimum 1 unit

Vacuum ejector with pad

- 1. a vacuum ejector with pad ø32~40mm
- 2. Built-in silencer.
- 3. Come with ISO symbol on component's body or component's mounted plate.
- 4. One-touch fittings for 4mm tube.
- 5. Quantity: Minimum 1 unit

Pressure indicator

- 1. Includes a red optical gauge with a display angle of 180°.
- 2. Come with ISO symbol on component's body or component's mounted plate.
- 3. One-touch fittings for 4mm tube.
- 4. Quantity: Minimum 1 unit

• Pneumatic counter

- 1. Pneumatic counter with preselection and resets facility.
- 2. Automatic or manual preselection.
- 3. Pneumatic signal once the amount of pulses selected has been reached.
- 4. Come with ISO symbol on component's body or component's mounted plate.
- 5. One-touch fittings for 4mm tube.
- 6. Quantity: Minimum 1 unit.

Stepper Module

- 1. Stepper Module A with simultaneous memory clearing
- 2. Each set consisting of 5 modules.
- 3. Pressure range: 0-9.9 kgf/cm2
- 4. Quantity: Minimum 1 unit.

Two Hand Control Valve

- 1. Operating pressure: 2.5 10 bar
- 2. Equipment having a safety circuit.
- 3. Applicable to Nylon and polyurethane tubing.

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302022, India.













4. Quantity: Minimum 1 unit.

Set of 4mm tubing.

1. Material: Polyurethane

2. Outer diameter: 4mm

3. 4mm blue tubing. Quantity: Minimum 10m.

4. 4mm white tubing. Quantity: Minimum 10m.

• "T" fittings 4mm

1. One touch "T" fitting for 4mm tubes.

2. Quantity: Minimum 10 units

Straight fittings 4mm

1. One touch straight fitting 4 x 4mm.

2. Quantity: Minimum 10 units

• Elbow fittings 4mm

1. One touch elbow fitting 4 x 4mm

2. Quantity: Minimum 5 units

Plastic plug 4mm

1. Tool for plugging pressure outlets in 4mm tube.

2. Quantity: Minimum 10 units

Blanking plugs with sealing ring

1. Threaded

2. Connection thread size: 1/8"

3. Quantity: Minimum 5 units

• Box with trays for basic pneumatics component

1. Box storage for basic pneumatics component.

2. Include with trays with identification labels.

3. Quantity: Minimum 1 unit

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777 India Sales: +91-9588842361



