

**Specifications:****● Air Filter Regulator**

1. Consisting of a filter, a regulator, and a 1 MPa pressure gauge.
2. 5µm filtering or better.
3. Includes a 3/2 discharge valve with silencer for connection and disconnection of the rest of the circuit.
4. Option of vertical and horizontal positioning.
5. Come with ISO symbol on component's body or component's mounted plate.
6. One-touch fittings for 4mm tube.
7. Quantity: Minimum 1 unit

● Manifold block

1. Includes minimum 8-outlet distribution block, one-touch fittings and non-return system.
2. Direct coupling to the air cleaning unit.
3. Come with ISO symbol on component's body or component's mounted plate.
4. One-touch fittings for 4mm tube.
5. Quantity: Minimum 1 unit

● Double acting cylinder

1. Stainless steel construction.
2. Diameter: Approximate 20mm ±10mm.
3. Max Stroke: 100mm ±10mm.
4. Provided with rubber cushion.
5. Come with ISO symbol on component's body or component's mounted plate.
6. One-touch fittings for 4mm tube.
7. Quantity: Minimum 2 units

● 3/2 single solenoid valve Normally Closed (NC)

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

1. Normally Closed (NC)
 2. Power consumption: Less than 0.6W.
 3. Provided with LED display and surge absorber.
 4. Spring and air reset.
 5. Come with ISO symbol on component's body or component's mounted plate.
 6. One-touch fittings for 4mm tube.
 7. Quantity: Minimum 1 unit
- **5/2 double solenoid valve**
 1. Power consumption: Less than 0.6W.
 2. Provided with LED display and surge absorber.
 3. Spring and air reset.
 4. Come with ISO symbol on component's body or component's mounted plate.
 5. One-touch fittings for 4mm tube.
 6. Quantity: Minimum 3 units
 - **5/2 single solenoid valve**
 1. Power consumption: Less than 0.6W.
 2. Provided with LED display and surge absorber.
 3. Spring and air reset.
 4. Come with ISO symbol on component's body or component's mounted plate.
 5. One-touch fittings for 4mm tube.
 6. Quantity: Minimum 2 units
 - **Power supply**
 1. Input voltage: 220V~240 VAC
 2. Output voltage: 24VDC
 3. Output current: 2.5A or higher.
 4. Safety socket terminal for connection.
 5. Minimum 8 socket connection for 24VDC terminal.
 6. Provided with protection against short circuits.
 7. Input switch and LED display.
 8. Supply cable included. Type 3 pin plug.
 9. Quantity: Minimum 1 unit
 - **Set of electrical inputs (Button pad with 3 pushbuttons)**
 1. Safety socket terminal for connection.
 2. Minimum 2 momentary push buttons
 3. Minimum 1 latch push button

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

4. Minimum 3 indicator lights
5. Minimum 2 NO and 2 NC contact for each pushbutton.
6. Quantity: Minimum 1 set.
- **Set of 3 relays**
 1. Safety socket terminal for connection.
 2. Minimum 3 relays
 3. Relays rating: 24VDC coil with 4 NO & 4 NC contact for each relay.
 4. Provided with relay active LED.
 5. Quantity: Minimum 1 set.
- **Set of Indicators**
 1. Safety socket terminal for connection.
 2. Indicators voltage rating: 24VDC
 3. Minimum 8 pilot lamps
 4. Minimum 1 buzzer
 5. Quantity: Minimum 1 set
- **Solid state/proximity switch**
 1. To be placed on cylinder.
 2. Operating voltage: 24VDC
 3. PNP output
 4. Includes LED display and connection cables.
 5. Quantity: Minimum 2 units.
- **Electrical end of stroke switch/limit switch**
 1. Includes roller-driven end of stroke with switchable electric contact.
 2. Minimum 1 NO & 1 NC
 3. Quantity: Minimum 3 units
- **Electrical contact pressure switch**
 1. Includes pneumatic-electrical converter.
 2. Pressure 0-8 bar adjustable.
 3. Pressure indicator display provided.
 4. Quantity: Minimum 1 unit
- **Set of 4mm tubing.**
 1. Material: Polyurethane
 2. Outer diameter: 4mm
 3. 4mm blue tubing. Quantity: Minimum 10m.
 4. 4mm white tubing. Quantity: Minimum 10m.

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com

- **Box with trays for basic electro-pneumatics component**

1. Box storage for basic electro-pneumatics component.
2. Include with trays with identification labels.
3. Quantity: Minimum 1 unit

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com