



An orifice is an opening made in the side or bottom of a tank, having a closed perimeter, through which the fluid may be discharged. A mouthpiece is a short tube fitted to a same size circular opening provided in a tank so that fluid may be discharged through it. Orifice and mouthpiece are used to measure the rate of flow of liquid. The apparatus is designed to measure the co-efficient of discharge of orifice & mouthpiece.

The apparatus consists of a supply tank, at the side of which a universal fixture for mounting orifice or mouthpiece is attached. A centrifugal pump supplies the water to the supply tank. Head over the orifice/mouthpiece is controlled by a by pass valve provided at pump discharge. A measuring tank is provided to measure the discharge. A gauge for measuring X and Y co-ordinates of jet from the orifice is provided, which is used to calculate C_v of orifice.

SPECIFICATIONS:

- Supply Tank - 0.4 X 0.3 X 0.5m height
- Orifice - 8mm and 10 mm.
- Mouthpiece
 - (a) L/D = 4
 - (b) L/D = 1
 - (c) Bordas mouthpiece.
 - (d) Convergent mouthpiece.
- X-Y gauge for orifice jet co-ordinates.
- Measuring tank of suitable capacity OR a calibrated water flow meter.
- Sump tank of suitable capacity.
- 0.5 HP pump with valve.

A technical manual accompanies the unit.

SERVICES REQUIRED:

- Flow surface 2 mtrs. X 1 mtr. X 1.5 mtrs. height.
- 230 Volts, 5 Amp. Stabilized AC. Power Supply.

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in