



Features:

- Wide range of accessories for basic experiments with airflow
- Record a fan characteristic
- Optional software for data acquisition

Tesca Principles of Air Flow Studies Apparatus allows experiments on the fundamentals of airflow. Optional software for data acquisition and visualization makes the experiments especially clear and enables fast execution of experiments with reliable results. The experimental unit includes a radial fan, which can be used to generate flow velocities up to 9m/s. An inlet contour on the intake side ensures a low-turbulence flow and thus a homogeneous velocity distribution in the measuring section. A throttle valve on the end of the pressure pipe can be used to adjust the airflow to allow the fan characteristic curve to be recorded. When used in conjunction with the power meter it is possible to determine the efficiency of the fan.

Further accessories for additional experiments can be attached in the intake pipe: electronic total pressure sensor, pressure distribution on a cylinder, and heat transfer at a cylinder in transverse flow. To study the friction losses, the intake pipe is replaced with pipe elements from (straight pipes, pipe bends, and pipe angles).

Measuring points along the measuring section allows temperature, pressure, and velocity measurements to be taken. The flow rate is determined by means of the inlet contour and the pressure measurement. The measured values are transmitted directly to a PC via USB. The data acquisition software can be included optionally

Specifications:

1. Investigation of the principles of airflow
2. Transparent intake pipe with mounting options for additional accessories
3. inlet contour minimizes turbulence on the intake side
4. Throttle valve on the delivery pipe to adjust the airflow
5. Electronic measurement of temperature and pressure

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tescaglobal.com



6. Determine velocity by means of the dynamic pressure
7. Determine flow rate via differential pressure
8. Optional Software for data acquisition via USB under Windows 7, 8.1, 10

Technical Specifications:

Radial fan

- Max. power consumption: 90W
- Speed: 2800min⁻¹
- Max. flow rate: 460m³/h
- Max. differential pressure: 480Pa

Delivery pipe

- Outer Ø: 110mm
- Inner Ø: 99,4mm

Intake pipe

- Outer Ø: 140mm
- Inner Ø: 134,4mm

Measuring ranges

- Pressure: Druck: 1x ±10mbar
- Pressure: 2x ±1mbar
- Temperature: 0...200°C

Experiments:

- Recording a fan characteristic
- In conjunction with the power meter HM 240.02
- Determining the fan efficiency
- In conjunction with corresponding accessories
- Velocity distribution in the pipe
- Velocity distribution behind a cylinder subject to transverse incident flow
- Pressure distribution around a cylinder subject to transverse incident flow
- Friction losses in pipes, pipe bends, and pipe angles
- Recording the cooling curve of a copper cylinder subject to incident flow
- Determining the heat transfer coefficients from the cooling curve

Requirements:

- Mains Input: 220 – 240V AC @ 50Hz

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tescaglobal.com

