

Experimental Training Board has been designed specifically for the study of the measurement of Percentage Modulation.

**Object:**

To measure Percentage Modulation using pentagrid mixer valve :

01. By Sine Wave method.
02. By Trapezoidal method.

**Features:**

The board consists of the following built-in parts :

- 01 A valve with base fixed on panel and wire internally.
- 02 Adequate no. of other electronic components.
- \* Adequate no. of patch cords stackable from rear both ends 4mm spring loaded plug length ½ metre.
- \* Good Quality, reliable terminal/sockets are provided at appropriate places on panel for connections/ observation of waveforms.
- \* Strongly supported by detailed Operating Instructions, giving details of Object, Theory, Design procedures, Report Suggestions and Book References.
- \* Weight : 3 Kg. (Approx.)
- \* Dimension : W 340 x H 110 x D 210

**Other Apparatus Required:**

- \* IC Regulated Power Supply
- \* Decade Audio Frequency Generator
- \* R. F. Signal Generator
- \* Cathode Ray Oscilloscope 20MHz

Note: Specifications are subject to change.

*Tesca Technologies Pvt. Ltd.*

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,  
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,  
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com  
Website: www.tesca.in

