

The trainer provides all necessary inputs and connection for students to study Pulse Code Modulation Transmission techniques. A communication link can be established by using PCM receiver.

Technical Specifications

: 16 MHz
: 2 KHz, 4 KHz (sine wave synchronized to sampling pulse Adjustable amplitude and separate variable
DC level)
: Two
: Time Division Multiplexing
: Pulse Code Modulation
: Pseudo random sync code generator
: Off - Odd - Even - Hamming
: Fast: 320 KHz/channel (approx.)
: 1.9 Hz/channel (approx.)
: Using 2 channels via RS232
: 9 Pin D type connector - 2Nos.
: Selectable from 300 to 2400
: 50
: 2 mm Sockets
: $220 V \pm 10\%$, 50 Hz/60 Hz on request
: 4VA(approx.)

- Crystal Controlled Clock
- On-board Sine wave generator (Synchronized)
- 2 TDM Analog Channels
- PCM Transmitter
- Fast & Slow modes for real time operation and data flow examination
- Error check code options (odd-even parity, Hamming Code)
- 4 Switched faults allow different Error Check Options
- PC PC Communication via RS232 interface

•

Experiments that can be performed

- Pulse Code Modulation
- A/D Converter, Parallel to Serial Data conversion
- Time Division Multiplexing of PCM Data
- Synchronization by Pseudo random Code
- Error Check Codes with switched faults
- Connecting modes between transmitters & receiver (1) Sync, clock, data lines connected (2) Clock, data connected (3) Data
- Study of the effect of induced faults
- PC-PC communication in 3 modes

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India, Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com Website: www.tesca.in

