**SALIENT FEATURES :**

- 01 Facilitates easy and safe wiring by students due to use of 4mm sturdy Shrouded banana patch cords & shrouded socket arrangements.
- 02 All machines are mounted on finely painted sturdy base frame with easy machine interchangeability. Use of gear coupling facilitates screwless coupling. interchangeability. Use of gear coupling facilitates screwless coupling.
- 03 With due emphasis on student safety machines operate upto 300W power levels and upto 1500 RPM, without compromising on didactic use. Able to draw all graphs.
- 04 Trunnion mounted DC Integrated machine is used as Dynamometer for loading other machines (Motors / generators both); unlike magnetic powder brake or eddy current brake which can load only coupled Motors and not generators, with facility to measure shaft power using electronic torque / speed Measurement

REPLUTION MOTOR TRAINER**Name of the Experiments :-**

- Experiment-1 Study of speed torque characteristics of Repulsion motor.
Experiment-2 Study of efficiency and input power factor measurement of single phase Repulsion motor.
Experiment-3 Speed control and reversal of direction of rotation of repulsion motor.

PANELS PROVIDED

- 01 Aluminum Machine trainer Rack
- 02 Multifunction Meter (Single Phase/Three Phase AC 50Hz)
- 03 DC voltmeter & Ammeter and Torque Measurement Meter
- 04 Variable DC Power Supply
- 05 Input Single Phase DOL Starter Panel AC DC Fix / Variable Supply
- 06 DC Load Resistor
- 07 Extension Board

MOTORS PROVIDED

- 1 Repulsion Motor with loading arrangement

ACCESSORIES PROVIDED

- 01 Hand held digital Tachometer
- 02 Shrouded connecting leads 4mm 50 / 100cm assorted Red & Black

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in

Technical Specification of Panels

MULTIFUNCTION METER (Single Phase/ Three Phase AC 50Hz)



- 1 Bidirectional Multifunction Meter
- 2 3 Phase 4 wire, 440V, Current 5A
- 3 LED display,
- 4 Aux supply 230V, 45-65Hz, 5W
- 5 To measure parameters ie Voltage Current., KVA, Frequency, Power factor, Active Power (W), Reactive Power (vary) etc.
- 6 Shrouded socket 08Nos. etc.

DC LOAD RESISTOR



- 1 750E/600E/300E/212E/162E/125E/112E/100E/400W /8 taps + OFF + separate 60E tap For DC series Gen.
- 2 Load Resistance switch 3 POL 7 Way/10Amp.
- 3 Cooling Fan size 4" 230V Operated
- 4 Shrouded socket 6Nos.

DC VOLTMETER & AMMETER WITH TORQUE MEASUREMENT METER



- 1 TWO DPM DC voltmeter (0-1000V)
- 2 TWO DPM DC Ammeter (0-20A)
- 3 Torque Measurement Meter
- 4 Shrouded socket 16Nos.

EXTENSION BOARD

- 1 Operating Voltage 230VAC \pm 10% at 50Hz
- 2 ON OFF Switch with indicator
- 3 Eight Nos. five pin 5 Amp Electrical Sockets

VARIABLE DC POWER SUPPLY



- 1 Half bridge SCR based 0V-200V / 3 Amp cosine firing with linear characteristics, 3 Nos. Switch SPDT to On/Off with indication
- 2 Three Nos. of these supplies required for DC Armature, DC motor field and AC generator field.
- 3 Shrouded socket 8Nos.

ALUMINUM FRAME - MODULAR PANELS




Electrical motor trainer rack made up aluminium profile size 40×40mm, foldable and light in weight 10 panel setup can be interchange conveniently to perform experiments. Dimension Length 1100×Height 1000×Depth 350mm.

INPUT SINGLE PHASE DOL STARTER PANEL AC DC FIX / VARIABLE SUPPLY



- 1 MCB 2 pole 10A with indicator
 - 2 Emergency Switch
 - 3 Push button switch for Stop/Start
 - 4 DOL 9A Contractor with 230V / 50 Hz / 11VA Coil .
 - 5 Shrouded socket 4Nos.
- Variable AC Supply (0-200V)**
1 Shrouded socket 6Nos.
- Fix/Variable DC Supply (0-200V)**
1 Shrouded socket 4Nos.

Technical Specification of Motor



REPULSION MOTOR(69307) WITH LOADING ARRANGEMENT

Voltage : 230 VAC, 50Hz

Capacity 300W/4 Pole m/c **RPM** 1500 **Terminals** 2

Rotor Construction : Standard commutator brush but short circuited.

Stator construction : Stator brought out on 2 terminals. Settable handle to rotate brush position w.r.t. Neutral axis.

Loading arrangement:

Friction brake pulley (60.5mm dia) for loading arrangement with 20Kg spring balance for torque measurement.

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in