



SPECIFICATIONS:

- Based On Siemens Logo And Logo Long PLC
- Internal SMPS Power Supply : 24V DC @ 1 Amp
- SPST Toggle Switch : 8
- Variable Potentiometer 10KOhm : 4
- LDR Sensor : 1
- PTC Thermistor : 1
- NTC Thermistor : 1
- Magnetic Switch : 2
- Output LED : 5
- Relay 24V DC 1 Changeover : 4
- DIN Rail : 1
- Push Button Switches NO : 2
- Push Button Switches NC : 2
- Relimate Connectors : 3
- Input Sockets 4mm : 8
- Output Sockets 4mm : 12
- Switch Power On/Off : 1
- Operating Voltage : 230V AC

EXPERIMENTS:

- To Study NO (Normally Open) And NC (Normally Close) Switch Function
- To Study Latching (Set) And Unlatching (Reset) Bit Function
- To Study AND Gate
- To Study OR Gate
- To Study NOT Gate
- To Study And Use Timer Instruction
- To Study And Use Counter Instruction
- To Study And Use Relay Logic
- To Study Working of Magnetic Switch

INCLUDED ACCESSORIES:

- USB Interfacing Cable
- Demo Software
- User Manual
- Patch Cords and PLC Connection Lead
- Mains Lead

NOT INCLUDED:

- Siemens Logo and Logo Long PLC

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in