



### Switch mode power supply

#### Technical specifications

Size (in mm)	:	190x140x60
No. of output	:	1
Input Voltage	:	85 264 V AC, 47 63 Hz
Output Voltage	:	24V DC, 4A
Power cord	:	3Pin , Type M
Protection	:	AC - 2A glass type fast blown fuse DC - 4A glass type fast blown fuse
Material	:	ABS



Note: Specifications are subject to change.

### **Tesca Technologies Pvt. Ltd.**

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,  
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,  
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com  
Website: www.tescaglobal.com

**Product List**

No.	Product Name	Qty.	Uom
2.1	Electro Pneumatic Compact trainer kit with PLC	1	Nos
2.2.1	Junction box with slide valve	1	Nos
2.2.2	FRCLM with pressure gauge	1	Nos
2.2.3	Miniature Single acting cylinder - Magnetic(Ø25x50)	1	Nos
2.2.4	Miniature double acting cylinder(Ø25 x 100)	1	Nos
2.2.5	Double foot mounting (Ø25)	2	Nos
2.2.6	5/2 Way Double solenoid pilot operated valve	1	Nos
2.2.7	3/2 Way NC Single sol. pilot operated valve with sp. return	1	Nos
2.2.8	Inline flow control valve	3	Nos
2.2.9	Union TEE fittings	2	Nos
2.2.10	Dummy Plug	2	Nos
2.2.11	Union Y Fittings	2	Nos
2.2.12	Ø4 PU tube	10	Mtr
2.2.13	Ø8 PU tube	0.5	Mtr
2.2.14	Tube cutter	1	Nos
2.2.15	Electrical Push Button Assy	1	Nos
2.2.16	Magnetic Sensor with clamp for Miniature DAC Cylinder	4	Nos
2.2.17	Electrical connection set-banana plugs and cables	1	Nos
2.2.18	PLC Assembly	1	Nos
2.2.19	Panel	1	Nos

Note: Specifications are subject to change.

**Tesca Technologies Pvt. Ltd.**

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,  
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,  
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com  
Website: www.tescaglobal.com