



The X-Y position control system module gives provision to interface PLC with two axis displacement and speed control.

Features

- Controlled by PLC
- Active area min.200mm*200mm
- Capable to draw shape such as straight line, inclined line, rectangle, square, pentagon, hexagon.

Experiments

- To draw straight line, inclined line, Square, Rectangle, Triangle, Hexagon, Pentagon with the help of PLC
- ladder program & XY position control module.

System Dimension

- Control Panel: 1.5Ft (L) X 1Ft. (W) X 1Ft. (H)
- X-Y Platform: 1.5 ft (L) × 1.5 ft (W) ×0.5 ft (H)

Services Required

- Electric Supply of 1φ 230 VAC motor.

Technical Specification		
No.	Item Name	Technical Specifications
1	Servo Motor	
2	Horizontal Platform	200 mm × 200 mm
3	Servo Amplifier	
4	PLC	Micrologix 1200 / Equivalent Digital inputs- 14, Digital outputs- 10 (Relay- 5, FET- 4, High Speed- 1). PC interface facility, PC-PLC interfacing cable. Ladder Programming Software.

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
 Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
 Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
 Website: www.tescaglobal.com