



Salient Features:

- Double walled design
- Inner chamber is made of mirror polished stainless steel material S.S. 304
- Exterior body is fabricated from Mild steel material which is powder coated in attractive shades
- The gap between the inner chamber and exterior body is filled with glass wool insulation to avoid thermal loss
- The bath is ARGON WELDED to ensure lifetime leakage free performance. (No soldering)
- Bath is fitted with specially designed Tubular Heating Element extending to the length of the bath for uniformity of temperature
- Bath Panel consists of 2 pilot LED lamps & on/off switch
- Bath is also equipped with a constant speed stirrer for uniform temperature distribution throughout the chamber.
- The stirrer with electric motor is mounted on the side of the bath at the top.
- The electric motor of the stirrer will be of Godrej / Crompton Greaves/ any other reputed make
- Stirrer paddles will be of stainless steel material to offer corrosion resistive performance.
- The stirrer is so fitted in such a way that, it does not obstruct the working area.
- Instrument is also equipped with drainage valve facility to empty the bath after the end of experiment.

Note : Water baths of higher capacity is also available. Price on request.

Technical Specification

Temperature Ranges	: From 5 °C above ambient to 100 °C
Temperature controller	: Digital Auto Tune PID Temperature Indicator cum Controller
Temperature Accuracy	: ± 0.5 °C
Operation on	: 230 Volts, 50 Hz, AC Supply
Working Area (L x B x D)	: 325 mm x 300 mm x 175 mm
No. of racks	: 04 Racks
Overall Dimensions	: 810 X 425 X 505 (L X W X D) mm

Note: Specifications are subject to change.