



TECHNICAL SPECIFICATIONS

- DC Power Supply IC Regulated +5V, $\pm 12V$ @ 500mA.
- DC Power Supply IC Regulated 0 to 30V @ 250mA
- DC Power Supply IC Regulated 0 to 15V @ 250mA
- DC Power Supply IC Regulated 0 to -15V @ 250mA
- AC Power Supply 12-0-12VAC
- Operated On Mains Power 230v, 50hz $\pm 10\%$
- Ammeter/Voltmeter 20mA/20VDC.
- Ammeter 2/200mA DC.
- Voltmeter 2/200VDC.
- Ammeter 1A AC.
- Voltmeter 15V AC
- Logic Inputs & Outputs 16 Bit
- Logic Low Frequency Mono Pulsar 2Nos.
- Frequency Generator 1Hz to 1MHz (Variable Frequency and Amplitude)
- Pulse Generator 1MHz Fixed
- Modulating Frequency: Amplitude and Frequency
- 2 Variable Resistors are given on Board.
- One Low Frequency Speaker.
- Buzzer as Continuity Tester.
- 2 BNC to Socket Adapter on Board.

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com