



Key features

- Compact Ergonomic Design.
- User Friendly, Self Explanatory Systems.
- Leak proof Safety Measures.
- Enhanced Electrical Safety Considerations.
- Training Manuals for Operation Ease.
- Inbuilt Safety Measures to avoid improper usage.
- Castor wheel mounted movable frame

Technical Specifications

- Level Tank - Dimension: 6"X 6"X24", Material P.P. 5mm thick, With Acrylic Front Fascia
- Sump tank - 24" x 24" x 15" Material: P. P
- Submersible Pump - Supply of 1 ϕ 230 VAC
- Differential Pressure Transmitter - Range: - 400 to 400 in H₂O, Output: 4-20 mA, 2-Wire HART Compatible
- Power supply: 24 V DC, 30 mA
- Level Indicator - 3 ½ Digit Display, Inbuilt 24VDC Supply, 1 ϕ 230 VAC Power Supply
- Control Panel - MS Powder Coated Frame with Indicator , Switches & Level Indicator on front fascia

Range of Experiments-

- STUDY OF LEVEL MEASUREMENT USING DPT.

System Dimension - 26" (L) X 18" (W) X 67" (H)

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com