

**Features:-**

- Certificates: CE, UKCA
- Languages: EN, FR, DE, IT, ES, SV, PL, CZ
- Contact and non-contact measurements
- MAX/MIN/AVG/HOLD
- Rotatable LCD backlight screen
- Unit conversion
- Bluetooth APP
- Auto power off
- Data storage
- Two measurement buttons

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



SPECIFICATIONS:-		RANGE
Non-contact (optical) measurement	Rotational velocity (RPM)	1-99,999
	Frequency (HZ)	1-1,666
	Count(REV)	1-99,999
	Target distance	50~500mm
Contact measurement	Rotational velocity (RPM)	1-19,999
	Frequency (HZ)	1-333
	Surface velocity	0.1m wheel
		0.1-1,999m/min
		0.4-6,550ft/min
		4-78,700in/min
		6"wheel
		0.15-1,524m/min
		0.5-5,000ft/min
		6-60,000in/min
	Length	0-99999(m/ft/in)
Accuracy	±0.02% ±1 digit	
Measurement modes	Contact RPM/Non-contact RPM/counting/frequency/Surface velocity/length	
Contact measurement unit	m/min, ft/min, in/min,m,ft,in	
Statistical measurement	Max/Min/Last reading/Average	
Data storage	10 groups	
Bluetooth APP	√ (iENV)	
Display	Rotatable LCD backlight screen	
Operating temperature/humidity	0°C~50°C;≤80%RH	
Storage temperature	-20°C~60°C;≤80%RH	
Drop Test	1m	
Auto power off	After about 15 minutes of inactivity	

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com