



### Technical Specifications

- Heavy ABS housing plus compact protective holster alongside
- High input impedance 20Kohm/DCV, 9Kohm/ACV Certificates with CE-EMC & LVD CAT II 1000V, CAT III 500V
- DCV test ranges: 0.1-2.5-10-50-250-1000V with accuracy <3% of F.S.; Null Center +/- DC 5V/25V with accuracy 5% of F.S.
- ACV test ranges: 10-50-250-1000V with accuracy <4% of F.S.
- DCA test ranges: 0.05-2.5-25-250mA, 10A with accuracy <3% of F.S.
- Resistance test Ranges: x1, x10, x100, x1K, X10K(20MΩ Max.) with accuracy <3% of Arc.
- Capacitance test Ranges: 0.0025-0.25-25uF with accuracy <3% of F.S. via CT-1; 2~2,000 uF approximate value (With Extra Kit)
- Other Tests including Dry Battery, Continuity Buzzer, Decibel, Diode, Transistor hFE etc.
- Dimensions & Unit Weight: 160(L) x 105(W) x 40(H) MM & 380g

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com