



Order Code : 20213521.2.15

Name : Rasberry pi 4 Model



Specifications:

Processor	Broadcom BCM2711, quad-core Cortex-A72 (ARM v8) 64-bit SoC @ 1.5GHz
RAM Memory	4GB LPDDR4 SDRAM
Connectivity	2 × USB 2.0 Ports 2 × USB 3.0 Ports 2.4 GHz and 5.0 GHz IEEE 802.11b/g/n/ac wireless LAN, BLE Gigabit Ethernet Bluetooth 5.0
Operating Power	5V 3A DC via GPIO Header 5V 3A DC via USB Type-C Connector Power Over Ethernet (PoE)-Enabled (requires separate PoE HAT)
GPIO	(Fully backward-compatible with previous boards) Standard 40-pin GPIO Header
Multimedia	H.264 (1080p60 decode, 1080p30 encode); H.265 (4Kp60 decode); OpenGL ES, 3.0 Graphics
Video and Sound	2 × micro HDMI ports (up to 4Kp60 supported) 2-Lane MIPI CSI Camera Port 2-Lane MIPI DSI Display Port 4-Pole Stereo Audio and Composite Video Port
Clock Speed	1.5 GHz
Micro-SD Card Slot	Yes (FAT32 format), support maximum 32G Micro SD Card Memory Features
Operating Temperature Range	0°C to 50°C
Dimensions (mm) LxWxH	85 × 56 × 19
Weight (gm)	52g
UPC	692759968863
Shipment Weight	0.155 kg
Shipment Dimensions	10 × 6 × 2 cm

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.

TESCA TECHNOLOGIES PVT. LTD.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302029, Rajasthan, India.
Ph/ Fax: 91-141-2771791, 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in