

**TEMP. COEFF OF RESISTANCE USING PLATINUM RES. THERMO****SCOPE OF LEARNING:**

- Study of Low Resistance Measurement by Carey Foster Bridge

**TECHNICAL SPECIFICATIONS:****Analog Meters:**

Galvanometer 30-0-30, 20uA/Div.

**Power Supplies:**

DC Power Supply +1.5V DC, 150mA

**Power Supplies:**

Operated on Mains power 230V, 50Hz  $\pm 10\%$

**Components are mounted on the panels are:**

- Dial Resistance (Two Dial)
- Unknown Resistor

**SALIENT FEATURES:**

- Front panel built with high class insulated Printed Circuit Board sheet with well printed circuits and symbols.
- Fuse for Short Circuit protection
- Instruction manual.
- Connections are brought out through 4mm Colored Sockets.
- Patch Cords 4mm.
- The trainer is housed in ABS Plastic cabinet.
- Size of the trainer set 12"x8"

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com



Order Code – 26279964.2  
TEMPERATURE COEFFICIENT OF  
RESISTANCE (PLATINUM RTD)

**ACCESSORIES:**

- Platinum Resistance Thermometer
- Hot Plate
- Steam Boiler With Cork
- Thermometer



*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com

CIN: U29309RJ2011PTC035213  
GSTIN: 08AADCT8576E1ZZ

Follow Tescaglobal



worlddidac

M E M B E R

