

**Technical Specifications:**

- **Drilling Capacity:** 25 mm
- **Milling Capacity:** 25 mm
- **Table Size:** 1120 × 260 mm (min)
- **Max Spindle to Table Distance:** 400 mm (min)
- **Motor Power:** 2200 W
- **Power Supply:** 400V / 50Hz
- **Max Surfacing Capacity:** 100 mm (min)
- **Gooseneck (Throat):** 610 mm (min)
- **Longitudinal Stroke (X-axis):** 600 mm (min)
- **Transverse Stroke (Y-axis):** 270 mm (min)
- **Vertical Stroke (Z-axis):** 400 mm (min)
- **Spindle Taper:** ISO 40
- **Speed Range:** 45 to 1660 rpm
- **Number of Speeds:** 11 (min)
- **Head Orientation:** 360°

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

Main Accessories Included:

- **Steel Milling Vice**
 - Jaw Width: 160 mm
 - Opening: 120 mm
 - Total Height: 150 mm
 - Adjustable base graduated through 180°
- **Collet Holder**
- **Collet Set** (Diameters: 4, 5, 6, 8, 10, 12, 14, 16 mm)
- **Tightening Tie Rod**
- **2 End Mill Shafts** with Support
- **Allen Keys:** Sizes 5, 6, 8, 10, 12
- **Flat Spanners:** 8/10, 17/19, 22/24 mm
- **Machine Anchor Rods** (Qty: 4) with Nuts and Washers

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com