



Technical Specifications:

- Overload protection and double-sided glass epoxy
- PCB Null DCV: DC $\pm 5V$ / $\pm 25V$, $\pm 5\%$
- FSD DCV: 0.1/2.5/10/50/250V/1000V, $\pm 4\%$
- FSD ACV: 10/50/250V/1000V, $\pm 5\%$
- FSD DCA: 50 μ A/2.5mA/25mA/250mA/10A, $\pm 4\%$
- FSD Resistance: $\times 1$ / $\times 10$ / $\times 100$ / $\times 1k$ / $\times 10k\Omega$ (0.2 Ω ~ 20M Ω)
- Capacitance: C1(R $\times 1k$): 2000 μ F (Approx.)
- Max. Battery Check: 1.5V/9V
- Transistor hFE
- Diode and LED Test facility
- Continuity with Beeper facility
- Safety Standard: CAT II 1000V and CAT III 500V
- Standard accessories with printed operation manual

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com