



Key Specifications

- **Total Dimensions:** 1200 × 750 × 1300 mm
- **Input Power:** Single-phase, three-wire AC 220V ±10%, 50Hz/60Hz
- **Power Capacity:** < 500 VA

Optional Components

- Computer and table
- PLC module
- Air compressor

Included Components

- Table-mounted model (supports entry-level PLCs like Siemens S7-200 Smart, Mitsubishi FX Series)
- Entry-level HMI (e.g., Siemens KTP 700 Basic)
- Field I/O modules
- PLC I/O modules
- 5/8 port Ethernet switch
- Automation modules:
 - Sensor module
 - Switchgear module

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

- Pneumatic solenoid module with cylinders
- Profinet Cat 6 cable
- Pneumatic components (valves, junction boxes)

Features

- **Portable:** Designed for classroom demonstrations
- **Hands-on Learning:** Includes complete electrical wiring with test points
- **Ergonomic:** Accommodates multiple students
- **Durable:** Powder-coated mild steel construction

Educational Use

Supports training in:

- Pneumatic system installation
- PLC programming
- Automatic control debugging

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com