



SALIENT FEATURES

- Auto Range function
- 8 Speed selection
- Direct Viscosity reading and temperature display
- Large bright back-light LCD Display
- Viscosity value is accurate to 2 decimals = 0.01 mpa.s
- With automatic scanning function, the instrument can automatically recommend a suitable combination of rotor and speed
- Can automatically display the range of viscosity that can be measured by the selected combination

Parameter	Details
• Model	• ACCUMEN
• Make	• ACCUMEN
• Measuring Range mpa.s	• 20~2,000,000 mpa.s
• Measurement Resolution	• 0.01 mpa.s (Full scale)
• Speed	• 0.3, 0.6, 1.5, 3, 6, 12, 30, 60 RPM
• No of Speed	• 8 speed settings
• No of Standard Spindle	• 4
• Display	• LCD
• Auto Scan Function	• Can automatically scan and recommend the preferred combination of rotor and speed
• Temperature Monitoring	• Optional - Feature available
• Measurement Accuracy	• $\pm 1\%$ F.S
• Repeatability	• $\pm 0.5\%$ F.S
• Output	• RS 232C Interface

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



<ul style="list-style-type: none"> • Power Supply 	<ul style="list-style-type: none"> • AC 220V / 50Hz
<ul style="list-style-type: none"> • Dimension 	<ul style="list-style-type: none"> • 300 × 300 × 450 mm
<ul style="list-style-type: none"> • Weight 	<ul style="list-style-type: none"> • 9 kgs

STANDARD ACCESSORIES

- 4 Spindles
- Spindle Guard Leg
- Power Cord
- Stand Set
- **Instruction Manual**



Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

