



## Digital Wheel Balancer

### Features:

- High accuracy main shaft ensures high precision balancing
- Suitable for various kinds of wheel structure (steel & alloy rims)
- Suitable for static/dynamic balancing with ALU programming for alloy rims
- Auto start/stop function
- Includes malfunction diagnosis and self-calibration function

### Technical Data:

- **Power Supply:** 220V/60 Hz/1 Phase
- **Power:** 0.25 Kw
- **Rim Width:** 1.5 to 12"
- **Rim Diameter:** 10" to 24"
- **Max Wheel Diameter:** 650 mm
- **Balancing Time:** 8 seconds
- **Balancing Speed:** 200 rpm
- **Balancing Precision:**  $\pm 1$  gm

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com



### Tyre Changer Model

#### Features:

- Foot valve adopts stainless steel valve rod

#### Specifications:

- **Power Voltage:**
  - 110V/60 Hz/1 Ph/1.1 Kw
  - 220V/50 Hz/1 Ph/1.1 Kw
  - 380V/60 Hz/3 Ph/0.75 Kw
- **Working Air Pressure:** 8.0 to -10 Bar (115 – 145 PSI)
- **Rim Diameter:** up to 18"
- **Rim Width:** 4" – 15"
- **Max. Wheel:** 38" (980 mm)
- **Average Rotate Speed:** 6.8 rpm
- **Shovel Force:** 2000 Kg
- **Net Weight:** 260/220 Kg ( Approx)

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com