

**SPECIFICATIONS:-**

- 4mm OD Push to Connect Fitting Push in Connector 1/4 NPT Male Air Fittings Pneumatic Fitting, 4MM Air Tube Fittings Air Line Fittings Quick Connect Air Hose Fittings for 3D Printer (2-Packs)
- Type: 4mm Tube Od x 1/4" NPT Thread Push to Connect Air Fittings; Body Style: Male Straight, quick and Reliable connections; Fluid Admitted: Air, Water (No Freezing)
- Pneumatic Fitting Working Pressure: 0-1.0mpa | 0-150psi; Proof Pressure: 3.0Mpa | 435psi; Negative Pressure: -100Kpa | -29.5 In Hg; Applicable: Pipe PU/ PA/ PE/ PVC; Working Temperature: 0-60°C | 32~140°F
- Body and collar are made of Nylon 6.6, gripping ring is stainless steel, D seal and O-rings are Nitrile- corrosion resistance, ductility; The Stainless steel gripping ring ensures excellent tube retention while the D seal within the fitting provides a positive seal on the O.D. of the tube in both static and dynamic positions, due to an optimized design of the fitting cavity.
- All items in Pneumatic composite range are silicone free, Elliptical sleeve help to connect tube easily by manual, no special tools required, Outside (Inside where applicable) hexagonal wrench tightening.
- This Quick fittings are only used for industrial automatic apparatus and can not be applied on any medicinal equipment.

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com