



Overview

Microplate Shaker offers a speed range of 200 to 1500 rpm for adjustable shaking control. It features 4 plates, allowing for efficient and simultaneous shaking of multiple microplates. Our shaker is equipped with a brushless DC motor for smooth and reliable operation. This unit ensures uniform mixing and shaking of samples for consistent results. It features an LCD that accurately shows the system status and parameters

TECHNICAL SPECIFICATIONS:-

- Speed range: 200 to 1500 rpm
- Amplitude: 3mm
- Timer: 1min to 99hr59min
- No of plates: 4 plates
- Power Consumption: 45W
- Power supply: AC110V~240V 50/60
- Dimensions: 280 × 270 × 140 mm
- Weight: 4kg

Features :

- >One-touch knob operation
- >Automatic false detection
- >Buzzer alarm function
- >Adjustable timer

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



Applications :

Microplate Shaker is used for uniform mixing and shaking of samples in laboratory applications. It is commonly used in research, diagnostics, and clinical laboratories



Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

