

**FEATURES:-**

- Pivot range of $\pm 45^\circ$ on both sides
- Easily readable angle scale supports precise work
- Mitre adjustment within seconds
- Protected vice spindle
- Solid machine chassis with drill holes on both sides for attaching the
- MSR material stand
- Long handle supports sawing without applying excessive force, includes
- integrated pushbutton (on/off)
- Automatic coolant pump switch-on during sawing
- Functional protection device, closed design, mobile
- Fast opening mechanism for optimal safety during cutting
- Centrally clamping vise, 4x guided with individually adjustable clamping jaws Cut always occurs in optimal position relative to
- workpiece
- Solid machine chassis
- Protected vice spindle
- Machine chassis sizes:
- - 546 x 620 x 801 mm

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

SPECIFICATIONS:-**Output**

Electrical connection - 400 V/3 Ph ~50 Hz

Motor output - 0.75 / 1.5 kW

Coolant pump motor 40 W

General Information

Cutting angle -45° to +45°

Cutting angle adjustment - Via rotating bearing block

Feed manual

Cutting speed - 19 / 38 rpm

Saw blade diameter - Ø 315 mm

- Internal Ø 40 mm

Vice jaw width - 135 mm

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com