



Order Code : 20213571.3

Name : LCR-Q Meter



Specifications:

Useful for measurement of winding inductance and resistance of coil, transformer, motors, wires, cables, relays, chokes etc. and capacitance of capacitors, wire, cables etc. Superior performance employing LSI IC's. Instant values of D factor measurement, cover wide measurement range 0.1 μ H - 2000H, 0.1pf - 20000 μ f, 0.10hm - 20M0hm.

- Instant value, simultaneous 'D' factor measurement.
- Superior performance employing LSI IC'S
- Wide range of component value display
- Better calibration accuracy 0.5% + 1 count
- Automatic frequency selection
- Exceptional stability

Specification	
Resolution	0.1 μ H/pf/W
Accuracy	$\pm 0.5\% + 1$ Digit
Range	0-2000H, 0-20000 μ Fd 0-20MW
Measurement	Remote Kelvin Sensing
Frequency	100Hz, 2 μ fd/2H &above 1KHz,Below 2 μ fd/2H
Source	AC 1 Vpp for L&C
Power	500mV DC for R
D Factor	230 V AC $\pm 20\%$ 50Hz
Guard	Provided
Terminal	Provided
Overall	255mm(W)X95mm(H)
Dimensions	220mm(D)
Weight	Less than 3 Kg

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.

TESCA TECHNOLOGIES PVT. LTD.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302029, Rajasthan, India.
Ph/ Fax: 91-141-2771791, 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in