



Parameter	Specification
Wavelength Range	800nm ~ 1700nm
Connector	FC/SC/ST
Detector Type	InGaAs
Power Measurement Range	-70dBm to +10dBm / -50dBm to +26dBm
Uncertainty	±5%
Calibration Wavelengths	850nm / 980nm / 1300nm / 1310nm / 1490nm / 1550nm / 1625nm / 1650nm
Display Resolution (Power)	Linear: 0.1% / Logarithmic: 0.01dBm
Visual Fault Locator (VF)	650nm ±30nm
VFL Output Power	2mW / 10mW / 30mW
Operating Modes	CW / 1Hz / 2Hz
Connector for VFL	FC/SC/ST
Power Supply	3 × AA Batteries / 1500mAh Rechargeable Lithium Battery (optional)
Automatic Shutdown Time	10 minutes
Continuous Working Time	≥120 hours (OPM Function)
Operating Temperature	-10°C ~ +50°C
Storage Temperature	-40°C ~ +70°C
Relative Humidity	0 ~ 95% (Non-Condensing)
Dimensions (L×W×H)	186mm × 100mm × 50mm
Weight	140g / 150g

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com