


**Specifications -**

- Absorption column
- Height: 2x 750mm, inner diameter: 80mm
- 2 pumps (absorption/desorption)
- max. flow rate: 17,5L/min
- max. head: 47m
- 1 pump (cooling)
- max. flow rate: 29L/min
- max. head: 1,4m
- Compressor
  - max. positive pressure: 0,5bar
  - max. flow rate: 34L/min
- Refrigeration capacity: 1432W at 5/32°C
- Refrigerant: R513A, GWP: 631
- filling volume: 600g
- CO<sub>2</sub>-equivalent: 0,4t
- Measuring ranges
- flow rate:
  - 0,2...2,4Nm<sup>3</sup>/h (air)
  - 50...600L/h (solvent)
  - 0,4...5,4L/min (CO<sub>2</sub>)
- Temperature: 2x -200...100°C, 3x 0...120°C, 4x 0...60°C
- Pressure: 1x 0...2,5bar, 1x -1...0,6bar
- Differential pressure: 2x 0...250mmWC
- CO<sub>2</sub>-content: 0...100vol%
  - 230V, 50Hz, 1 phase
  - 230V, 60Hz, 1 phase; 230V, 60Hz, 3 phases
- UL/CSA optional
- Dimensions and Weight

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com