



Specification

Pitot Tubes are manufactured as per standards or as per the given design/drawing, with specified length and material of construction.

Construction

- L-Shaped design.
- Concentric tube type Pitot tube.
- Curved joint and ellipsoidal nose.
- Suitable for clear Air/Gas applications.
- Most widely used Pitot tube configuration.

Insertion Length

- 200 mm

Material of Construction (MOC)

- SS 304 Stainless Steel

Tube Dimensions

- Pipe O.D.: 3/8"
- Pipe I.D.: 1/4"

Pressure Connection

- 1/4" BSP (Female) or as required

Process Connection

- Nil

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com



Features

- Rugged SS 304 construction for corrosion resistance and long service life.
- Designed for accurate velocity and flow measurement in air and gas applications.
- Concentric tube construction with ellipsoidal nose for reliable pressure sensing.
- Available as per standard design or customized drawing requirements.
- Compact L-shaped configuration for convenient installation and operation.

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

