

**Description:**

- Sand Cone Density Apparatus (165) Is A 1 Gal (3.8L) Threaded Glass Jar With Detachable Metal Double Cone Fitting.
- The Cone Is Threaded On One End, Flanged To 165mm On The Other, With A Cylindrical Valve Of 12.7mm Dia.
- Orifice Between Ends. Valve Has Stops To Prevent Rotating Past Completely Open Or Closed Positions. Glass Jar For Sand Cone Density Test Is Available As A Replacement.

**Features:**

- Detachable Cone Fitting 1gal Capacity
- Valve Stop Prevents Rotating Past The Open Or Closed Position.
- Included Accessories: In-Place Density Accessory Kit With Components Needed For Density Testing
- Glass Jar Only As A Replacement Product
- 300mmx300mm Density Plate Only Fits The Sand Cone Of The Plastic Jar For Filling Test Hole With Density Sand

**Specifications:**

- Standard : Aashto T191,Astm D1556/1556m
- Capacity : 1gal (3.8 L)
- Diameter : Bottom Funnel Inside:165mm

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com