



### Specifications

- **Capacity:** 0 to 6 MPa
- **Minimum Division Value:** 0.001 MPa
- **Test Area Options:**
  - 7.3 cm<sup>2</sup> (<D30.5 mm)
  - 10 cm<sup>2</sup> (<D35.7 mm)
  - 50 cm<sup>2</sup> (<D79.8 mm)
  - 100 cm<sup>2</sup> (<D112.8 mm)
- **Thickness of Rubber Diaphragm:** ≤ 2 mm
- **Pressure Speed:** 100 ml/min to 500 ml/min
- **Accuracy:** ±1 mm, when the height at burst is up to 70 mm
- **Testing Units:**
  - kPa
  - kgf/cm<sup>2</sup>
  - atm
  - mmHg
  - lb/in<sup>2</sup> (free shift)
- **Output:**
  - Printer
  - Display output
  - Can be connected to a computer
- **Dimension:** 550 × 450 × 700 mm (L × W × H)

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com

- **Instrument Weight:** Approx. 100 kg

**Accessories**

- Test sets: Different sizes for various fabric types (7.3 cm<sup>2</sup>, 10 cm<sup>2</sup>, 50 cm<sup>2</sup>, 100 cm<sup>2</sup>)
- Rubber Diaphragms
- Calibration Tools
- English operation software
- Cable connects with PC

*Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.*



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com